

## GearLub

Wheel flange fluid grease for crane tracks and wheels.

Article No.: 3113

### Area of use



### Description

GearLub reduces the roll and slide friction between the wheels and the track that occurs under extreme pressure loadings. The wear is significantly reduced.

### Properties

- Application temperature: -20°C to +100°C
- Consistency: NLGI 00
- forms an insoluble and extremely strong and dry adhering lubrication film on metal surfaces, even with small dosages
- remains resistant over a long period, even under extreme pressure and heat loading
- thereby guarantees constant lubrication
- specially selected solid lubricant components make it possible to apply a fine lubrication and separation film between the friction parts.

Detailed data sheet and MSDS

[data@igralub.ch](mailto:data@igralub.ch)

#### Disclaimer

**"CAUTION: DO NOT USE THIS PRODUCT WITHOUT FIRST CONSULTING AN IGRALUB APPLICATION EXPERT"**

IGRALUB products are designed to be used under specific conditions, which require the appropriate applications are ensured by the user. Consult a designated IGRALUB application expert before use. IGRALUB disclaims all warranties of merchantability and fitness for a particular purpose where a designated and qualified application expert is not consulted prior to use. All sales are subject to IGRALUB's standard terms and conditions which can be found at: [www.igralub.com](http://www.igralub.com)