

RailLub[®] 30/40

Environmentally friendly wheel flange lubricant, liquid.

Article No.: 1343

Area of use



Tested by CEC-L-33-A-93



Carrier liquid: 90% degradable

Description

RailLub 30/40 consists of chemically treated solid lubricants and a solvent-free, synthetic carrier agent. It reduces the wear in the operation of rail vehicles that run at extremely low temperatures.

Properties

- Application temperature: -30°C to +80°C
- forms a strongly adhering lubrication film on metal surfaces
- resistance is guaranteed at a constant function from -60°C to +200°C
- contains no solvents and can be applied to -40°C
- prevents icing from interfering with the function during the winter.

Application

RailLub 30/40 can be processed manually or via automatic wheel flange lubrication systems.

Detailed data sheet and MSDS

data@igralub.ch

Disclaimer

“CAUTION: DO NOT USE THIS PRODUCT WITHOUT FIRST CONSULTING AN IGRALUB APPLICATION EXPERT”

IGRALUB products are designed to be used under specific conditions, which require the appropriate applications are ensured by the user. Consult a designated IGRALUB application expert before use. IGRALUB disclaims all warranties of merchantability and fitness for a particular purpose where a designated and qualified application expert is not consulted prior to use. All sales are subject to IGRALUB's standard terms and conditions which can be found at: www.igralub.com