

RailLub[®] 90/CR

Environmentally friendly high-tech wheel flange lubricant for cranes.

Article No.: 1943

Area of use



Tested by OECD 301 B



- easy biodegradability (93% in 28 days)

Description

RailLub 90/CR reduces the roll and slide friction between the wheels and the track that occurs under extreme pressure loadings. The wear is significantly reduced.

Properties

- Application temperature: -30°C to +200°C
- Consistency: NLGI 000
- forms an insoluble and extremely strong and dry adhering lubrication film on metal surfaces, even with small dosages
- this film also remains resistant over a long period, even under extreme pressure and heat loading and thereby guarantees constant lubrication
- It allows the specially selected solid lubricant composition of a transfer of a thin lubricating and release film between the friction parts.

Application

RailLub 90/CR can be applied manually or with wheel flange lubrication systems for cranes, gantry cranes, sliding platforms, etc.

Detailed data sheet and MSDS

data@igralub.ch

Disclaimer

"CAUTION: DO NOT USE THIS PRODUCT WITHOUT FIRST CONSULTING AN IGRALUB APPLICATION EXPERT"

IGRALUB products are designed to be used under specific conditions, which require the appropriate applications are ensured by the user. Consult a designated IGRALUB application expert before use. IGRALUB disclaims all warranties of merchantability and fitness for a particular purpose where a designated and qualified application expert is not consulted prior to use. All sales are subject to IGRALUB's standard terms and conditions which can be found at: www.igralub.com